

Electric battery operated Mobile Crane Max. Capacity Lbs. 4,950







OUTREACH (Ft)	CAPACITY (Lbs.)
3	3,000
4,5	1,800
8	1,000





TECHNICAL DATA

CRANE FRAME: three-wheelers frame fabricated from preformed and welded steel plate with built-in counterweight.

TRACTION: by AC 3kw 48V reversible electric motor, controlled by inverter, electro magnetic control on disk brake.

BATTERY: 48V 200Ah battery, battery meter on dashboard.

DRIVE: by 180° steering rudder. Steering 700W 48V electric motor electronically controlled. Complete with safety device on reverse.

WHEELS: nr. 1 rear cushion 305x135 e Nr. 2 front 18x7-R8 superelastic.

BOOM: three hydraulically telescoping sections with sequential hydralic telescope by double internal cylinder fitted with nylon wear pads. Adjustable wear pads on the sides.

BOOM CONTROL: by electronic proportional joystick distributor. 4 kW 48V motor pump.

LMI: electronic Load Moment Indicator. Display showing lifted load, max allowed load, tilting percentage, operating radius, angle, telescope and light indicators on the operative mode.

TOTAL WEIGHT: approx. Lbs. 4,300 nearly MAX. CAPACITY: Lbs. 4,950

Options on request: hydraulic winch; special oversized hydraulic winch; chain hoists; carry-deck; battery charger (on board and stand-alone); manual and hydraulic jibs; radio remote control; low temperatures kit; non marking tires.








- VALLA mobile crane mod. 25 EL complies with the following standards: -2006/42/CE -UNIEN13000
- -I.S.P.E.S.L.


VALLA


25EL


CAPACITY DIAGRAM (lb)

DIAGR. Nº 25E-005















Valla a division of CVS Ferrari Srl Via Piacenza, 45 - 29010 Calendasco (Piacenza) - ITALIA Tel. +39 0523 762025 / 752004 - Fax +39 0523 760531 e-mail: info@valla.com - www.valla.com