

70 mt *(75 USt)* Telescopic Crawler Crane

Remarkable control, reliability and capacity performance

- Diesel powered by Caterpillar C6.6 with 186.4 kW (250 hp)
- Variable displacement piston type main pumps with total horsepower control
- Main hoist's powered through piston motors & winch planetary drums grooved for 19mm (3/4") wire rope with 7 656.6 kg (16,880 lbs) available line pull
- 150 m/mm (492 fpm) line speed
- · Mechanical drum rotation indicators

Full power boom with attachment flexibility

- Full power 11.8 m to 35.2 m (38 ft to 115 ft) four-section boom
- Two boom extend modes: Exclusive A-max mode offers substantially increased capacities in close. Standard "B" mode extends all four sections equally.
- Maximum boom/jib length is 37.2 m + 17.7 m (122 ft + 58 ft) = maximum total attachment length 54.6 m (179 ft)
- Lightweight nylon head sheaves reduce overall machine weight and increase lift capacities
- Quick reeve boom head with quick reeve block allows rope to be easily reeved over boom head
- Hammerhead boom nose allows operator to work at high boom angles
- Optional 10.7 m to 17.7 m (35 ft to 58 ft) two-piece on-board lattice fly with 2°, 15°, 30° and 45° offsets
- Greaseless wear pads
- Optional auxiliary sheave off main boom

Ouick mobilization & superb iob-site mobility

- Transports COMPLETE IN ONE OR TWO LOADS
- Hydraulic retractable side frames for transport
- Fold-up catwalks
- Fast and easy hydraulic counter weight removal
- 100% self-assembly





Retracted travel gauge - 2.56 m (8'5") Intermediate working gauge - 3.63 m (11" 11")

Fully extended working gauge - 4.27 m (14)

Link-Belt Construction Equipment Company Lexington, Kentucky | www.linkbelt.com

@ Link-Belt is a registered trademark. Copyright 2009. All rights reserved. We reserve the right to change designs and specifications at any time. Litho in U.S.A. 3/10~#4377 (supersedes #4361)





