

Madal MD-25

Tabela de Cargas

Raio m	Distância da Lança									
	9,68 7 cabos		15,98 6 cabos		22,28 4 cabos		22,28 1 cabos		9,68 + 22,28	
	Graus	T	Graus	T	Graus	T	Graus	T	T	
2,0	70°	23,0								12,5
2,5	66°30'	23,0								12,5
3,0	63°	23,0								12,5
3,5	60°	20,4	72°30'	15,3						11,4
4,0	56°30'	18,0	70°	14,0						9,2
4,5	52°30'	15,8	68°30'	12,9						7,4
5,0	49°	13,7	66°30'	11,7	73°30'	7,5				6,1
6,0	40°30'	11,2	62°30'	9,7	71°	7,5				4,4
7,0	30°	8,8	58°30'	8,5	68°	6,8				3,3
8,0	14°30'	6,2	54°	6,6	65°	5,9				2,5
9,0			50°	5,3	62°30'	5,2	70°	2,3		1,9
10,0			45°	4,3	60°	4,6	68°	2,1		1,4
12,0			33°	3,0	53°	3,4	64°	1,9		0,8
14,0			16°	2,1	46°30'	2,5	59°30'	1,7		0,3
16,0					39°	1,9	55°	1,5		
18,0					30°	1,5	50°	1,2		
20,0					16°30'	1,1	45°	1,1		
22,0							39°30'	0,9		
24,0							33°	0,8		
26,0							25°	0,6		