

EZ REACH



Standard Features

- 42 ft. working height
- 300 lbs. bucket capacity
- 21 HP Diesel engine
- Radio Remote drive
- Insulated to 46 KV category C
- Full continuous rotation
- Full 360° work zone stability
- 180 degree rotating platform
- Hydraulic extended tracks
- Hydraulic tool outlets at bucket
- Unitrol control handle in bucket (available in 3 or 4 function)
- 28 ft. 1 in. horizontal reach

Dimensions

- Overall, length including aerial is 16ft.8 in.
- Length with outriggers fully extended is 14 ft. 4 in.
- Overall, width without tracks extended 35 in.
- Overall, height including aerial is 7 ft. 2 in.

Options

- Lower Tool Circuit
- Outrigger interlocks
- High Resistance Unitrol control handle in bucket

- Dual Pin Retention
- Will go through 36" gate
- E-power at bucket
- Lower Weight
- Torque Strips on all critical fasteners
- Two-speed track drive
- Upper & lower bucket dump
- Fully Hydraulic Extensions
- 5 lbs. per square inch ground pressure
- Unit is fully insulated in the retracted position
- No mandatory rebuilds
- 1 year warranty

Trailer

- GVWR: 10,000lbs.
- Hinged heavy duty loading ramps
- Electric Brakes
- 2 axles
- 60" x 18" x 10" tool box

