



CARY-LIFT 304-IMT

304-IMT

Performance

Maximum Lifting Capacity

-21,500 lbs (9,752 kg)

Maximum Lift Height

-14' (4.3 m)

Maximum Forward Reach

-10'1" (3.1 m)
(from tires)

Below Grade Reach

-4.5" (0.1 m)

Frame Leveling

-10° of Leveling (5° L/R)

Turning Radius

-25'5" (7.8 m)

Fuel Capacity

-95 Gallons (360 L)

Maximum Travel Speed

-22.3 mph (35.9 km/h)

Options

- Air Conditioning
- Light Packages
- Rear View Camera
- Additional Options Available

Standard Equipment

Engine

- Cummins QSC 8.3 L Turbo Diesel
- 240 hp
- Electronic Control and Protection

Transmission

- Dana 6000 Powershift
- Four Speed Forward and Reverse

Axles

- AxleTech Planetary Front and Rear
- Four-wheel Drive

Tires

- 29.50 x 29, 34 ply
- Interchangeable

Steering

- Four-wheel, Two-wheel and Crab Steer

Brakes

- Four-wheel Outboard Dry Hydraulic Disc

Hydraulic System

- Gear Pumps
- 10 Micron Filtration
- 135 Gallon (511 L) Reservoir

Cab

- Unmatched Visibility
- Large Tinted Safety Glass
- Adjustable Suspension Seat with Seat Belt
- Tilt/Telescopic Steering Column
- Full Set of Gauges for Instant Machine Status
- All-weather Cab

Controls

- Multi-function Proportional Joysticks



CARY-LIFT 304-IMT**Dimensions**

Height (carry position)
-13'4.8" (4.1 m)

Height (max raised position)
-19'10.5" (6.1 m)

Length (carry position)
-34'2.5" (10.4 m)

Length (max raised position)
-39'10" (12.1 m)

Width
-11'11" (3.6 m)

Wheel Base
-14'5" (4.4 m)

Ground Clearance
-2'2" (0.7 m)

Curb Weight (approximate)
-98,000 lbs (44,452 kg)

Attachment Features

- 41" to 164" Grip Range
- Continuous Tire Pad Rotation
- 12" of Side shift (6" L/R)
- Hydraulically Activated
Anti-Fallback Arms
- Dual Attachment Mounted
Cameras

Contact Information

Pettibone
1100 Superior Avenue
Baraga, MI 49908
800.GO.PETTIBONE

www.GoPettibone.com

