




Standard



Optional



1S

	1865	1200	840	kg
	2.00	3.22	4.60	m
510 kg 1120 lb	4110	2645	1850	lb
	6'6"	10'6"	15'1"	ft

2S

	1800	1135	785	595	kg
	2.00	3.28	4.66	6.09	m
550 kg 1210 lb	3970	2500	1730	1310	lb
	6'6"	10'9"	15'3"	19'11"	ft

3S

	1735	1080	740	555	415	kg
	2.00	3.35	4.72	6.15	7.57	m
580 kg 1275 lb	3825	2380	1630	1220	915	lb
	6'6"	10'11"	15'5"	20'2"	24'10"	ft

4S

	1680	1030	705	520	400	300	kg
	2.00	3.41	4.78	6.21	7.63	9.05	m
635 kg 1395 lb	3700	2270	1550	1145	880	660	lb
	6'6"	11'2"	15'8"	20'4"	25'00"	29'8"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
1S	3,86	380	1700	1965	515	2886 4066	3,5-5
2S	3,73	380	1700	1965	515	2886 4066	3,5-5
3S	3,62	380	1700	2020	535	2886 4066	3,5-5
4S	3,51	380	1700	2070	535	2886 4066	3,5-5

MODEL							
	lb*ft	(°)	in	in	in	in	lb
1S	27930	380	67	77	20	114 160	7700 11000
2S	26990	380	67	77	20	114 160	7700 11000
3S	26190	380	67	80	21	114 160	7700 11000
4S	25400	380	67	82	21	114 160	7700 11000