


NATIONAL CRANE

Subsidiary of Kilde, Inc.
KIDDE

General Offices:
11200 North 148th Street • Waverly, NE 68462
(402) 786-2240
Telex 438061



NATIONAL SERIES 800B TELESCOPING CRANES

Load Ratings for Available Boom and Jib Options

National reserves the right to change designs, prices and specifications at any time without notice.

Printed in USA Form No. S800BLR3873M © 1987 National Crane

Boom and Jib Combinations

Telescoping Booms

- Model 839B: 22- to 39-foot two section
- Model 856B: 22- to 56-foot three section
- Model 875B: 22- to 75-foot four section*
- Model 875BA: 22- to 75-foot four section*

*The Series 875BA is designed for National's self stowing auger.

Jib Options

- Model 8FJ21: 21-foot straight (for Models 839B, 856B, 875B)
- Model 8FJ5M: 21- to 35-foot manual pull-out (for all 800B Models)
- Model 8FJ5M: 21- to 55-foot manual pull-out (for Model 875B)
- Model 8FJ15A: 15-foot angling jib (for Models 856B, 875B, 875BA)

The capacities shown will be reduced when accessories are attached to the boom or loadline

Important Information and Cautions

Do not operate cranes or accessories within 10 feet of live power lines.

- 1 Load ratings shown on these charts are maximum allowable loads with the outriggers properly extended on a firm, level surface and the crane leveled and mounted in a factory-recommended configuration
- 2 Always level the crane with the level indicator on the crane frame
- 3 The operator must reduce loads to allow for factors such as wind.
- 4 Overloading the crane may cause structural collapse or instability
- 5 Weights of any accessories attached to the boom or loadline must be deducted from the load chart capacities.
- 6 Do not exceed jib capacities at any reduced boom length

NATIONAL SERIES 800B WINCH DATA

CAUTION

- Do not deadhead lineblock against boom tip when extending boom.
- Keep at least three wraps of load line on drum at all times.
- Use only the specified cable on this machine.

Winch	Cable Supplied	Average Breaking Strength	Lift and Speed				
			1 Part Line	2 Part Line	3 Part Line	4 Part Line	5 Part Line
Standard Planetary Winch	9/16" diameter rotation resistant	35,000 lbs.	7,000 lbs. 150 fpm	14,000 lbs. 75 fpm	21,000 lbs. 50 fpm	28,000 lbs. 37 fpm	35,000 lbs. 30 fpm
			Data applies to all 800B booms				
With Optional Burst-of-Speed Feature**	Same as corresponding cable data shown above	29,750 lbs.	3,000 lbs. 240 fpm	6,000 lbs. 120 fpm	9,000 lbs. 80 fpm	12,000 lbs. 60 fpm	15,000 lbs. 48 fpm
			†Applicable to the 875B boom Speeds shown are the same for all Series 800B booms.				
	Optional 9/16" diameter 6 x 25 IWRC		7,500 lbs.* 8,400 lbs.† 150 fpm	15,000 lbs.* 16,800 lbs.† 75 fpm	22,500 lbs.* 25,000 lbs.† 50 fpm	30,000 lbs.* 34,000 lbs.† 37 fpm	35,000 lbs.* 35,000 lbs.† 30 fpm

All winch pulls and speeds are shown on the third layer (the fourth layer on 875B). Winch pulls would increase on the first and second layers. Winch line speeds would decrease on the first and second layers. Winch line pulls may be limited by the winch capacity or the cable safety factor. These are shown below.

Winch
With standard rotation resistant rope 10,200 pounds
With optional 6 x 25 IWRC rope 10,200 pounds
*This feature is available with either the standard or optional cable. Ratings are based on intermittent use. High cycle applications may require optional oil cooler.

Bare Drum Pull
Cable Pull 8,400 pounds
Allowable 7,000 pounds

