



Drive options available


 **SHUTTLELIFT®**

Carrydeck® Industrial Crane

3300 & 5500 Series



The 5550RT Carrydeck Crane



Comfortable operator's cab

**Versatile, Productive
Cranes for Complete
Industrial Mobility**



The 3330ELB Carrydeck Crane

General Description

The Carrydeck line of industrial cranes from Shuttlelift, Inc. offers you a durable, versatile and productive crane in a compact design. Featuring complete mobility with a telescoping boom and a convenient load deck, Carrydeck industrial cranes have a profile advantageous for indoor and outdoor use.

| | 3330E | 3330ELB | 5540 | 5550RT |
|--|---|--|---|---|
| Max Capacity: 5' Radius, on Outriggers, 360° 6' Radius, on Outriggers, 360° | 17,000 lbs. - | 17,000 lbs. - | - 30,000 lbs. | - 30,000 lbs. |
| Max. Boom Lengths: (☉ of rotation to front side of block) 3-Section Boom 4-Section Boom | 18' 4" 24' 8" | 27' 2" 36' 8" | 36' 6" NA | NA 40' 4" |
| Jibs: Length Offset | 8' 0°-30°-45° | 10' 0°-30°-45° | 15' 0°-30°-45° | 15' 0°-30°-45° |
| Boom Elevation: | 60° | 60° | 80° | 80° |
| Carrydeck Capacity: | 14,000 lbs. | 14,000 lbs. | 20,000 lbs. | 20,000 lbs. |
| Engine: Cummins Diesel 4b3.9, 4 Cylinder | 71 HP | 71 HP | 76 HP | 100 HP Turbo |
| Transmission: ITL Powershift, 4-Speeds Forward and Reverse | PS 720 | PS 720 | PS 740 | PS 740 |
| Max. Travel Speed: | 22 mph | 22 mph | 18.2 mph | 22 mph |
| Steering: Wheels | 2 or 4 | 2 or 4 | 2 or 4 | 2 or 4 |
| Drive: Axle | Front | Front | Front std. Rear opt. | Front and Rear |
| Turning Radius: (☉ to outside wheel) 2-Wheel Steer 4-Wheel Steer | 14' 8" 10' 2" | 14' 8" 10' 2" | 21' 6" 12' 4" | 21' 6" 12' 4" |
| Wire Rope: | 7/16" EIPS IWRC 6 x 19 | 7/16" EIPS IWRC 6 x 19 | 1/2" EIPS IWRC 6 x 19 | 1/2" EIPS IWRC 6 x 19 |
| Tire Size: | 10.00 x 15 14 PR | 10.00 x 15 14 PR | 15.00 x 22.5 16 PR | 15.00 x 22.5 16 PR |
| Dimensions: Overall Length - Transport Position Overall Height - Transport Position Overall Width - Outriggers Retracted Weight | 12' 11" 7' 10" 6' 7" 14,250 lbs. | 16' 3" 7' 10" 6' 7" 17,280 lbs. | 21' 8" 7' 11" 7' 10" 25,800 lbs. | 19' 1" 7' 11" 7' 10" 29,500 lbs. |

AUTHORIZED REPRESENTATIVE



Leading the Way in Material Handling.

SHUTTLELIFT, INC., P.O. Box 66, Sturgeon Bay WI 54235

Telephone: 920-743-8650 Fax: 920-743-1522



E-Mail: lifts@shuttlelift.com Web-site: www.shuttlelift.com
©1997 SHUTTLELIFT, INC., STURGEON BAY, WI 54235