



ET36KX

FEATURES

- * 6,000 lb. Maximum Lifting Capacity
- * 36,000 ft.-lb. Moment Rating
- * Electric-Hydraulic Power
- * Hexagonal Boom Construction
- * Fully Hydraulic Boom Extension 10-20 ft.
- * High Efficiency Planetary Winch
- * Continuous Power Rotation
- * Load-Holding Counterbalance on All Cylinders
- * Meets ANSI B30.5 Safety Standards
- * Meets OSHA 1910.180 Requirements

STANDARD EQUIPMENT

- * Capacity Overload Shut-Off System
- * Anti-Two-Blocking System
- * 80 ft. of 5/16" Aircraft-Quality Wire Rope
- * Remote Control Pendant: 25 ft. Cord and Quick Disconnect
- * Snatch Block with Swivel Hook Safety Latch
- * Master Disconnect Switch
- * Battery Cable: 25 ft.

MINIMUM REQUIREMENTS

- * 11,100 lb. GVWR Chassis
- * Outriggers: Rear
- * Electric Power Source: 12V DC

LIFTING CAPACITIES	
REACH (FT.)	CAPACITY (LBS.)
6	6,000
10	3,600
16	2,250
20	1,800

OPTIONAL EQUIPMENT

- * Radio Remote Controls
- * Electric/Hydraulic and Manual Outrigger Packages
- * Mounting Pedestal for Platform Bodies
- * Boom Rests

Specifications subject to change without notice.



12110 Best Place Cincinnati, OH 45241
 800-226-2238 internetsales@venturo.com
 www.venturo.com

DISTRIBUTED BY:

