

# SPD 360 C+ SPD 360 CDH



3960 lbs



8'6" - 27'11"



6'11" - 11'2"

SPD360C+: 5280 lbs SPD360CDH: 5060 lbs		-	2T-D7: 22 lbs	JIB600M: 220 lbs
	10'2"x2'7"x6'6"		SPD360C+: 0.62 MPH SPD360CDH: 1.12 MPH	
	4180 lbs		6.26 PSI	20°
	3kW 24V-DC SEP n°4 6V-420 Ah			
	<b>SPD360CDH</b> Engine: 3 cylinders water cooled diesel, KUBOTA mod. D722-E3B, 2 rpm levels, EPA TIER 4 Motore: 3 cilindri diesel raffreddato a liquido, KUBOTA mod. D722-E3B, 2 livelli di regime, EPA TIER 4 Motor: Wassergekühlter 3 Zylinder Diesel Motor, KUBOTA mod. D722-E3B, 2 rpm, EPA TIER 4 Motor: Diesel 3 cilindros con refrigeración por aire, KUBOTA mod. D722-E3B, 2 niveles rpm, EPA TIER 4 Moteur: Diesel 3 cylindres, refroidissement à eau, KUBOTA mod. D722-E3B, accélérateur à 2 niveaux, EPA TIER 4			
	4kW 240V-60Hz-AC 1F		110 lbs	
<b>Telescopic Boom:</b> 1 base and 4 telescopic sections high-tensile structural steel. All sections synchronized and full power. <b>Braccio Telescopico:</b> 1 braccio principale e 4 telescopici in acciaio strutturale ad alta resistenza. Sfilo completamente idraulico e sincronizzato. <b>Teleskopausleger:</b> 1 Hauptausleger + 4 Hochwiderstand Stahl Teleskopausleger. Voll hydraulischer und teleskopierbarer Ausleger. <b>Pluma Telescópica:</b> 1 pluma principal y 4 telescópicas en acero de alta resistencia. Elementos sincronizados e hidráulicos. <b>Flèche Téléscopique:</b> 1 flèche principale et 4 téléscopiques en acier à haute résistance. Eléments synchronisés et hydrauliques.				
	360° 1.5 rpm		0°/70° 14"	
	6'11" - 27'11" 26"		1320 lbs - 196' - Ø5/16 in SPD360C+: 52 ft/min SPD360CDH: 45/90 ft/min	

