


340.00

EFFER


340.00



Standard



Optional



56

3S

	13200	7870	5270	3920	3140	kg
	2.27	4.06	5.97	7.97	10.04	m
	3615	29100	17350	11615	8640	lb
	7965	75"	13'3"	19'7"	26'1"	ft

4S

	12800	7520	5020	3710	2860	2380	kg
	2.27	4.16	6.06	8.06	10.14	12.31	m
	3810	28215	16575	11065	8175	6305	lb
	8395	75"	13'7"	19'10"	26'5"	33'3"	40'4"

5S

	12650	7250	4820	3490	2680	2160	1790	kg
	2.27	4.30	6.20	8.20	10.28	12.45	14.68	m
	4005	27885	15980	10625	7690	5905	4760	lb
	8825	75"	14'1"	20'4"	26'10"	33'8"	40'10"	ft

4S+JIB 3S

	1270	1110	1000	900	kg
	15.17	16.77	18.43	20.12	m
	2795	2445	2200	1980	lb
	49'9"	55'	60'5"	66'	ft

	1860	1475	1200	1000	kg
	5.85	7.45	9.14	10.83	m
	4100	3250	2645	2200	lb
	19'2"	24'5"	29'11"	35'6"	ft

4S+JIB 4S

	1200	1030	900	810	735	kg
	15.25	16.85	18.51	20.20	21.90	m
	2645	2270	1980	1785	1620	lb
	50'	55'3"	60'8"	66'3"	71'10"	ft

	1740	1365	1090	940	810	kg
	5.93	7.53	9.22	10.91	12.60	m
	3835	3005	2400	2070	1785	lb
	19'5"	24'8"	30'2"	35'9"	41'4"	ft

MODEL							
	txm	(°)	mm	mm	mm	mm	t
3S	32,27	407	2450	2500	1230	6400	26
4S	31,51	407	2450	2500	1230	6400	26
5S	31,44	407	2450	2550	1230	6400	26
4S+JIB 3S	31,51	407	2550	2550	1320	6400	26
4S+JIB 4S	31,51	407	2550	2550	1320	6400	26

MODEL							
	lb*ft	(°)	in	in	in	in	lb
3S	233490	407	96	98	48	252	57300
4S	227990	407	96	98	48	252	57300
5S	227480	407	96	100	48	252	57300
4S+JIB 3S	227990	407	100	100	52	252	57300
4S+JIB 4S	227990	407	100	100	52	252	57300