

# REACH STACKER RSD 4520TL

LIFTING CAPACITY with toplift (spreader)

	RSD4520-5TL
1 st. row, 2,0 m	45t,4 high
	24t,5 high
2 nd row, 3,85 m	31t,3 high
	27t,4 high
3 rd row, 6,4 m	16t,3 high

## VEHICLE WEIGHT

	Unloaded	Loaded (41t)
With toplift (TL)		
front/kg	34000	94500
rear/kg	37000	17500
total/	71000	112000

## LIFTING HEIGHT

Under twistlocks/m	
RSD 4520-5	14,7

## PERFORMANCE

Lifting speed	
loaded/unloaded m/s	0.20/0.22 appr.
Lowering speed	
loaded/unloaded m/s	0.25/0.20 appr.
Travel speed	
loaded/unloaded km/h	22/25 appr.
Gradeability	
loaded/unloaded %	20/34 appr.

## DIMENSIONS

Transport height/mm	4400
Transport length/mm	11120 (with spreader)
Width /mm	4200
Turning radius /mm	8250 appr.

## ENGINE

	<i>ENGINE # 2354416</i>
Make-model	<i>4/94</i> Cummins LTA10C
Type	4-stroke diesel, turbocharged
Displacement/l	10.0
Power DIN 6270B	200 kW (278 hp) at 2100 r/min
Max. torque/Nm	1280
No. of cylinders	6
Compression ratio	16,3
Generator	75A/24V
Equipment	Dry air cleaner, double fuel filter

## TRANSMISSION

Make-model	Clark 34000-series
Clutch type	Torque converter
Gear box	Power Shift
No. of gear	4-4
Gear shifting	
Electric	24V

## AXLES

Front axle	Planetary driving axle, with hub reduction
Rear axle	Valmet steering axle, with 2 steering cylinders

## BRAKES

Service brakes	Wet multidisc brakes on the drive axle
Parking brake	Dry spring actuated disc brake on the drive line

## WHEELS

Front	18.00-33 40 PR
Rear	18.00-33 40 PR

## HYDRAULIC SYSTEM

Pumps	Two twin intra vane pumps
System pressure	210 bar
Control valves	Loadsensing proportional valves for the boom
Filtering	10-micron return line filter
Tank capacity	500 l

## OPERATORS CAB

Heavy steel construction with a roof window, effectively sound insulated Sliding movement 1850 mm, controlled from the drivers cab.  
Adjustable seat with damping  
Effective heater/ defroster with suction air filtering  
Windshield wipers and washers on front, rear and roof windows.  
Controls for the engine, boom and spreader.

## BOOM

Welded steel construction with square cross section, telescoping type  
Lifting angle 0...60 deg.  
Lifting cylinders Two cylinders, equipped with safety valves

## SPREADER

Hydraulically adjustable for ISO and Sealand 20', 30', 35' and 40' containers.  
Welded steel construction with square cross section two telescopic extensions on both sides  
Rotation +200° /- 100°  
Sideshift +/- 800mm  
Tilting +/- 4 deg. free tilting  
Damping with hydraulic Twist locks, with safety devices

## STANDARD EQUIPMENT

Gauges: Hour meter, fuel and engine temperature  
Indicator lights: Charging, engine temperature and oil pressure, transmission temperature and pressure, brake system pressure, parking brake, gear disengagement, driving lights, head lights, turn signals.  
Lights: Driving lights, turning signals, cab light, working lights on the boom (4), backing lights  
Warning: Flashing lights (2) on the boom, horn  
Stability control: Electronic overload control system  
Fire extinguisher: 6kg  
Other: Engine block heater (220 V), mirrors

**ROTATION SPEED**

Runway (max.)	2200...2300 RPM
Idling	650...700 RPM
STALL	1750 ± 150 RPM

**STALL-test**

Resulting from the hydrodynamics mode of action of the converter, the rotation speed of the turbine wheel changes according to the burden of the outlet shaft.

When the burden gets bigger, rotation speed gets lower, but simultaneously torque gets bigger. If the turbine is stalled to stop, the torque is at its biggest. The converter is then operating in so called STALL-state.

In this case, as the pumping wheel is pushing oil through the stopped turbine wheel, oil gets heated quickly.

STALL - test is also used when defining condition of the engine or gearing. If STALL-rating is smaller than the announced STALL-rating, the fault must be locked for in the engine.

If STALL-rating is bigger, the fault must be locked for in the gearing.

**CARRYING OUT THE TEST**

Lock the brakes. Set change-over of direction lever to position for driving IV. Accelerate the engine to the highest rotation speed.

**NOTE!** *Do not use STALL-rotation with full acceleration for long time, because torque-converter overheats. Maximum operating time 30 seconds.*